

## ➤ TABLE OF STANDARD PROPERTIES OF USE AND MEASUREMENT

The properties defined in the table below, are set up according to the technical conditions of use and measurement. These properties are warranted within their variation range and in compliance with the standard technical conditions of use.

Properties PPA80XL	Standard technical conditions	Unit	Nominal values	Min. values	Max. values
Notes		-	Preliminary data	-	-
Max. no load displacement	Quasistatic excitation, blocked-free	μm	76	68	87
Blocked force	Quasistatic excitation, blocked-free	N	7000	5600	8400
Stiffness	Quasistatic excitation, blocked-free	N/μm	92,11	73,68	101,32
Resonance frequency (free-free)	Harmonic excitation, free-free, on the admittance curve	Hz	6500	5525	7150
Response time (free-free)	Harmonic excitation, free-free, on the admittance curve	ms	0,08	0,07	0,09
Capacitance	Quasistatic excitation, free-free, on the admittance curve	μF	48,00	43,20	62,40
Max. tensile force	Static effort, blocked-free	N	1800	1350	1800
Resolution	Quasistatic excitation	nm	0,76	-	-
Height (in actuation direction)		mm	100,00	99,80	100,20
Depth (base)		mm	30,00	29,80	30,20
Width (base incl. wedge & wires)		mm	30,00	29,80	30,20
Mass		g	319,0	-	-
Standard mechanical interface (top)	1 centered M5 threaded hole 6 mm deep & 4 M3 threaded holes on Ø 20 mm 6 mm deep	-	-	-	-
Standard mechanical interface (base)	1 centered M5 threaded hole 6 mm deep & 4 M3 threaded holes on Ø 20 mm 6 mm deep	-	-	-	-
Standard electrical interface	2 PTFE insulated AWG30 wires 100 mm long with Ø 1 banana plug	-	-	-	-

## ➤ PROPERTIES STANDARD TECHNICAL CONDITIONS OF USE AND MEASUREMENT

<b>Free-free</b>	: The actuator is not fixed
<b>Blocked-free</b>	: The actuator is fixed to a mechanical support assumed infinitely stiff
<b>Quasistatic excitation</b>	: AC voltage between -20 and 150 V at 1 Hz
<b>Harmonic excitation</b>	: Voltage of 0.5 Vrms, sinusoidal mode from 0 to 100 kHz
<b>Max. harmonic excitation</b>	: Voltage defined by the measurement of max. displacement, sinus at resonance frequency
<b>Displacement measurement</b>	: Laser interferometer, capacitive displacement sensor
<b>Admittance measurement</b>	: HP 4194 A electrical impedance analyser
<b>Environment</b>	: Ambient temperature (15-25°C) and dry air (Humidity < 50 % rH)

Any technical conditions of use, different from those defined above, can lead to temporary or definitive alterations of properties. Thank you to contact CEDRAT TECHNOLOGIES before using actuators under non standard technical conditions.

## ➤ FACTORY TESTS CARRIED OUT

- Test 1 : Electrical admittance vs. Frequency, free-free
- Test 2 : Displacement vs. input voltage

## ➤ EXTRA FACTORY TESTS

- Test 3 : Gain and linearity of the sensor
- Test 4 : Step response in closed loop
- Test 5 : Stability in closed loop

## ➤ MECHANICAL INTERFACE

- |  |   |  |
|--|---|--|
| <input type="checkbox"/> [ FI ] Flat Interface   | <input type="checkbox"/> [ H ] Flat Interface with hole | <input checked="" type="checkbox"/> [ TH ] Flat Interface with threaded hole |
| <input type="checkbox"/> [ SV ] Specific version | <input type="checkbox"/> [ FF ] Free-free Interface     | <input type="checkbox"/> [ SI ] Specific interface                           |

## ➤ AVAILABLE OPTIONS

- |  |  |  |
|--|--|--|
| <input checked="" type="checkbox"/> [ SG ] Strain gauges | <input type="checkbox"/> [ CS ] Capacitive displacement sensor | <input type="checkbox"/> [ NM ] Non-magnetic |
| <input checked="" type="checkbox"/> [ VAC ] Vacuum       |  |  |